



Swivel castor PA/RU Ø 100 mm - with ball bearing, 160 kg

SKU 48055

This swivel castor is equipped with a ball bearing with a diameter of 100 mm. The material of the rim consists of polyamide (PA) and the tread of rubber. The wheel is sound-absorbing, streak-free and equipped with a load capacity of 160 kg.

TECHNICAL DATA

Castors diameter mm	100
Material	Rubber
Status	New
Outside dimension length	100
Outside dimension height	128
Carry weight	160
Product	new
Type	Wheels

APPLICABLE SERVICES



REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

PRODUCT DESCRIPTION

A swivel wheel with a load capacity of 160 kg. The tread of the wheel consists of blue rubber (RU) and the material of the rim of black polyamide (PA). The steel of the transport wheel is electrolytically galvanized. The diameter of the wheel is 100 mm and the height of the castor wheel is 128 mm. The center hole diameter of the swivel wheel is 8 mm and the temperature range is -20° C to + 60° C. The wheel is equipped with a mounting plate with dimensions 104 x 80 mm. The bolt hole is 9 mm and the hole pattern has the dimensions 80 x 60 mm. The wheel is also sound-absorbing and streak-free! The wheels of LogistiekOnline can be combined with various types of roll containers and dollies . Would you like to know more about the different types of roll container wheels and applications or tips when purchasing ? Then read our blog!



Link to visit this page:

<https://rotom.co.uk/swivel-castor-pa-ru-o-100-mm-with-ball-bearing-160-kg-48055>

