



APPLICABLE SERVICES



REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

Swivel castor PA/RU Ø 125 mm - with ball bearing, blue, 200 kg

SKU 48059

This swivel castor has a ball bearing with a diameter of 125 mm. The material of the rim consists of polyamide (PA) and the tread of rubber. The wheel is sound-absorbing, streak-free and equipped with a load capacity of 200 kg.

TECHNICAL DATA

Castors diameter mm	125
Material	Rubber
Status	New
Outside dimension length	125
Outside dimension height	155
Carry weight	200
Product	new
Type	Wheels

PRODUCT DESCRIPTION

A swivel castor with a load capacity of 200 kg. The tread of the wheel consists of blue rubber (RU) and the material of the rim of black polyamide (PA). The steel of the transport wheel is electrolytically galvanized. The diameter of the wheel is 125 mm and the height of the castor wheel is 155 mm. The center hole diameter of the swivel wheel is 10 mm and the temperature range is -20° C to + 60° C. The wheel is equipped with a mounting plate with dimensions 104 x 80 mm. The bolt hole is 9 mm and the hole pattern has the dimensions 80 x 60 mm. The wheel is also sound-absorbing and streak-free! The wheels of LogistiekOnline can be combined with various types of roll containers and dollies. Would you like to know more about the different types of roll container wheels and applications or tips when purchasing? Then read our blog!

Link to visit this page:

<https://rotom.co.uk/swivel-castor-pa-ru-o-125-mm-with-ball-bearing-blue-200-kg-48059>

