



**Swivel castor inhibited 100mm diameter with ball-bearing - PP / TPR**

SKU 48122

Swivel wheel with brake and ball bearing provided with gray PP core and thermoplastic rubber tread, diameter of the caster wheel is 100 mm. The caster has a load capacity of 135kg.

**TECHNICAL DATA**

|                                 |        |
|---------------------------------|--------|
| <b>Castors diameter mm</b>      | 100    |
| <b>Material</b>                 | PP     |
| <b>Status</b>                   | New    |
| <b>Outside dimension length</b> | 110    |
| <b>Outside dimension width</b>  | 80     |
| <b>Outside dimension height</b> | 110    |
| <b>Dynamic load</b>             | 135    |
| <b>Product</b>                  | new    |
| <b>Type</b>                     | Wheels |

**APPLICABLE SERVICES**



**PRODUCT DESIGN**

We can design and produce similar custom made product for you.



**REPAIR AND MAINTENANCE**

This product can be repaired or maintained. Contact us for more details

**PRODUCT DESCRIPTION**

**100mm braked castor wheel with ball-bearing - PP / TPR**

One standard wheel for roll containers which has a loading capacity of 135kg, and is therefore suitable for a normal load. The caster wheel has a weight of 0.85kg and is made of a gray PP plastic core and a gray TPR tread. TPR stands for thermoplastic rubber, it is sound-absorbing, but not such as in a rubber tread. The bearing of the wheel is a ball bearing. Temperature range in which the wheel can be used is -6 & deg; C to + 80 & deg; C The hole pattern has dimensions 80x60mm, provided with holes for bolts 9 mm. NOTE: Maximum load capacity of four wheels is however approximately 500kg frame of the cart must also be suitable for 500kg

[Link to visit this page:](#)

<https://rotom.co.uk/swivel-castor-inhibited-100mm-diameter-with-ball-bearing-pp-tpr-48122>

