



## Transport wheel PU Ø 150 mm - with ball bearing, 250 kg

SKU 48400

The diameter of this transport wheel is 150 mm and it has a polyamide core, with a polyurethane tread. The load capacity is 250 kg. A sturdy wheel with a soft and durable tread for comfortable use on slippery floor surfaces.

### TECHNICAL DATA

<b>Castors diameter mm</b>	150
<b>Material</b>	PU
<b>Status</b>	New
<b>Outside dimension length</b>	150
<b>Outside dimension height</b>	150
<b>Carry weight</b>	250
<b>Product</b>	new
<b>Type</b>	Wheels

### APPLICABLE SERVICES



#### REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

### PRODUCT DESCRIPTION

This transport wheel for roll containers has a load capacity of 250 kg, making it suitable for medium-heavy loads. The core is made of polyamide and the tread of injected polyurethane. The core features ball bearings and the diameter of the ball bearing fit is 47mm. The tread is soft and durable with a tread width of 45 mm. The wheel diameter is 150mm, the core diameter is 135mm and the tread hardness is 70° - 80° Sh.A. In short, this is a high-quality wheel that is streak-free, has a wide temperature range and has a durable ball bearing. In addition, this wheel can be mounted under every roll container and dolly in our range. Temperature range in which the wheel can be used is -20°C to +70°C. Look here if you want to read more about different types of roll container wheels and applications.

[Link to visit this page:](#)



<https://rotom.co.uk/transport-wheel-pu-o-150-mm-with-ball-bearing-250-kg-48400>

