



APPLICABLE SERVICES



REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

Swivel castor PU Ø 150 mm - with ball bearing, 250 kg

SKU 48401

This swivel castor is equipped with a ball bearing with a diameter of 150 mm. The polyurethane tread of the castor wheel guarantees low rolling resistance and quiet running! The load capacity is 250 kg.

TECHNICAL DATA

Castors diameter mm	150
Material	PU
Status	New
Outside dimension length	150
Outside dimension width	45
Outside dimension height	190
Carry weight	250
Product	new
Type	Wheels

PRODUCT DESCRIPTION

This swivel castor has a load capacity of 250 kg, making it suitable for medium-heavy loads. The tread of the wheel consists of injected polyurethane with a core of high-quality polyamide. As a result, the swivel wheel guarantees a low rolling resistance and low-noise running. In addition, the wheel is wear-resistant and streak-free! The wheel comes with mounting plate with the dimensions 135 x 110 mm. The axle hole diameter is 20 mm and the overall height of the castor wheel is 190 mm. This wheel has a tread width of 45 mm and the center distance of the mounting holes is 105 x 80/75 mm. The tread hardness is 70° - 80° Sh.A, the mounting holes are 11mm in diameter and the internal fork width dimension is 63.5mm. The material of the fork (type: MD50) consists of galvanized steel and the temperature range of the wheel is -20°C to +70°C. The construction is equipped with a central kingpin, making it very suitable for regular peak loads! These castor wheels with polyurethane tread are suitable as an alternative to vulcanised natural rubber, when certain chemicals, oils and greases play a role. In addition, this wheel can be mounted under every roll container and dolly in our range. Look here if you want to read more about different types of roll container wheels and applications.

Link to visit this page:

<https://rotom.co.uk/swivel-castor-pu-o-150-mm-with-ball-bearing-250-kg-48401>

