



Fixed castor PU Ø 150 mm - with ball bearing, 250 kg

SKU 48402

This fixed castor has a ball bearing with a diameter of 150 mm. The polyurethane tread is of the best quality and guarantees quiet running. The load capacity of this fixed castor is 250 kg.

TECHNICAL DATA

Castors diameter mm	150
Material	PU
Status	New
Outside dimension lenght	150
Outside dimension width	45
Outside dimension height	190
Carry weight	250
Product	new
Type	Wheels

APPLICABLE SERVICES



REPAIR AND MAINTENANCE
This product can be repaired or maintained. Contact us for more details

PRODUCT DESCRIPTION

This fixed castor has a load capacity of 250 kg, making it suitable for medium-heavy loads. The tread of the wheel consists of injected polyurethane with a core of high-quality polyamide. As a result, the fixed castor guarantees low rolling resistance and low-noise running. In addition, the wheel is wear-resistant and streak-free! The wheel comes with mounting plate with the dimensions 135 x 110 mm. The bore diameter is 20 mm and the height of the fixed castor is 190 mm. This wheel has a tread width of 45 mm and the center distance of the mounting holes is 105 x 80/75 mm. The tread hardness is 70° - 80° Sh.A, the mounting holes are 11mm in diameter and the internal fork width dimension is 63.5mm. The material of the fork (type: MD50) consists of galvanized steel and the temperature range of the wheel is -20°C to +70°C. The rim material is made of plastic and the adhesion to the core is perfect! This transport wheel is hygienic and maintenance-



free, making it widely used in food industries. In addition, this wheel can be attached under any roll container and dolly in our range. Fixed castors with a polyurethane tread are suitable as an alternative to vulcanized natural rubber, when certain chemicals, oils and greases play a role. Look here if you want to read more about different types of roll container wheels and applications.

[Link to visit this page:](#)

<https://rotom.co.uk/fixed-castor-pu-o-150-mm-with-ball-bearing-250-kg-48402>

