



APPLICABLE SERVICES



REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

Transport wheel PU Ø 200 mm - with ball bearing, 450 kg

SKU 48404

This transport wheel has a diameter of 200 mm and has a polyamide core, with a polyurethane tread. The load capacity is 450 kg. A sturdy wheel with a soft and durable tread for comfortable use on slippery floor surfaces.

TECHNICAL DATA

Castors diameter mm	200
Material	PU
Status	New
Outside dimension length	200
Outside dimension width	50
Outside dimension height	200
Carry weight	450
Product	new
Type	Wheels

PRODUCT DESCRIPTION

This strong transport wheel has a load capacity of 450 kg. The tread of the wheel is made of injected polyurethane, with a core of polyamide. Because the tread is soft and very durable, it guarantees excellent driving comfort on slippery floor surfaces! The axle hole diameter of this loose transport wheel is 20 mm, the tread width is 50 mm. The diameter of the ball bearing fit is 47mm and the depth is 17mm. The installation length of the wheel is 54 mm. The hub diameter of the transport wheel is 69 mm and the hub length is 60 mm. The wheel is wear-resistant and elastic. The temperature range is -20°C to +70°C and its own weight is 1.39 kilograms. The hardness of the tread is 70° - 80° Sh.A. In addition, this wheel can be mounted under every roll container and dolly in our range. Read our blog about different types of roll container wheels and applications here.

Link to visit this page:

<https://rotom.co.uk/transport-wheel-pu-o-200-mm-with-ball-bearing-450-kg-48404>

