



Swivel castor PU Ø 200 mm - with ball bearing and brake, 450 kg

SKU 48407

This swivel castor has a ball bearing with a diameter of 200 mm. The polyurethane tread of the castor wheel guarantees low rolling resistance and quiet running! The load capacity is 450 kg.

TECHNICAL DATA

Castors diameter mm	200
Material	PU
Status	New
Outside dimension length	200
Outside dimension width	50
Outside dimension height	238
Carry weight	450
Product	new
Type	Wheels

APPLICABLE SERVICES



REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

PRODUCT DESCRIPTION

This swivel castor has a load capacity of 450 kg, making it suitable for heavy loads. The tread of the wheel consists of injected polyurethane with a core of high-quality polyamide. As a result, the castor wheel guarantees low rolling resistance and low-noise running. In addition, the wheel is wear-resistant, streak-free and equipped with a foot brake at the rear! The wheel comes with mounting plate with the dimensions 135 x 110 mm. The axle hole diameter is 20 mm and the overall height of the castor wheel is 238 mm. This wheel has a tread width of 50 mm and the center distance of the mounting holes is 105 x 80/75 mm. The tread hardness is 70° - 80° Sh.A, the mounting holes are 11mm in diameter and the internal fork width dimension is 63.5mm. The material of the fork (type: MD50) consists of galvanized steel and the temperature range of the wheel is -20°C to +70°C. The construction is equipped with



a central kingpin, making it very suitable for regular peak loads! These castor wheels with polyurethane tread are suitable as an alternative to vulcanised natural rubber, when certain chemicals, oils and greases play a role. In addition, this wheel can be mounted under every roll container and dolly in our range. View our blog about different types of roll container wheels and applications here.

[Link to visit this page:](#)

<https://rotom.co.uk/swivel-castor-pu-o-200-mm-with-ball-bearing-and-brake-450-kg-48407>

