



## Transport wheel PU Ø 125 mm - with ball bearing, 400 kg

SKU 48408

This loose wheel is equipped with a ball bearing with a diameter of 125 mm. The polyurethane tread of the wheel guarantees low rolling resistance and quiet running! The load capacity is 400 kg.

### TECHNICAL DATA

|                                 |        |
|---------------------------------|--------|
| <b>Castors diameter mm</b>      | 125    |
| <b>Material</b>                 | PU     |
| <b>Status</b>                   | New    |
| <b>Outside dimension length</b> | 125    |
| <b>Outside dimension width</b>  | 40     |
| <b>Outside dimension height</b> | 125    |
| <b>Carry weight</b>             | 400    |
| <b>Product</b>                  | new    |
| <b>Type</b>                     | Wheels |

### APPLICABLE SERVICES



#### REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

### PRODUCT DESCRIPTION

A strong transport wheel that has a load capacity of 400 kg. This makes it extremely suitable for both light and medium-heavy transport, even on less slippery floors! The wheel tread is made of cast polyurethane (PU) with a cast iron core (painted black). The hardness of the tread is 90° - 98° Sh.A (HARD). As a result, the transport wheel guarantees low rolling resistance and low-noise running. The wheel is also wear-resistant and streak-free. The axle hole diameter of this loose wheel is 20 mm and the height is 125 mm. This wheel has a tread width of 40 mm and the weight of this transport wheel is 1.46 kg. The temperature range of the wheel is -30°C to +80°C. This transport wheel with polyurethane tread is suitable as an alternative to vulcanized natural rubber when certain chemicals, oils and greases play a role. In addition, this wheel can be mounted under every roll container and dolly in our range. Would you like to learn more about points to consider when buying wheels? Then read



our blog with tips when purchasing !

Link to visit this page:

<https://rotom.co.uk/transport-wheel-pu-o-125-mm-with-ball-bearing-400-kg-48408>

