



Transport wheel PU Ø 150 mm - with ball bearing, 650 kg

SKU 48412

This loose wheel is equipped with a ball bearing with a diameter of 150 mm. The polyurethane tread of the wheel guarantees low rolling resistance and quiet running! The load capacity is 650 kg.

TECHNICAL DATA

Castors diameter mm	150
Material	PU
Status	New
Outside dimension length	150
Outside dimension width	50
Outside dimension height	150
Carry weight	650
Product	new
Type	Wheels

APPLICABLE SERVICES



REPAIR AND MAINTENANCE
This product can be repaired or maintained. Contact us for more details

PRODUCT DESCRIPTION

This strong transport wheel has a high load capacity of 650 kg, making it extremely suitable for heavy transport. The wheel tread is made of cast polyurethane (PU) with a cast iron core (painted black). The hardness of the tread is 90° - 98° Sh.A (HARD). As a result, the transport wheel guarantees a low rolling resistance and low-noise operation. The wheel is also wear-resistant, streak-free and resistant to various oils, minerals, greases and hydrolysis. The axle hole diameter of this loose wheel is 20 mm and the height is 150 mm. This wheel has a tread width of 50 mm and the weight of this transport wheel is 3.24 kg. The temperature range of the wheel is -30°C to +80°C. This transport wheel with polyurethane tread is suitable as an alternative to vulcanized natural rubber when certain chemicals, oils and greases play a role. This wheel has a perfect balance between driving comfort and heavy duty applications. In addition, this wheel can be mounted under every roll container and dolly



in our range. Would you like to learn more about points to consider when buying wheels? Then read our blog with tips when purchasing !

[Link to visit this page:](#)

<https://rotom.co.uk/transport-wheel-pu-o-150-mm-with-ball-bearing-650-kg-48412>

