

PRODUCT SPECIFICATION SHEET



APPLICABLE SERVICES



REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

Swivel castor PU Ø 150 mm - with ball bearing, 500 kg

SKU 48413

This swivel castor is equipped with a ball bearing with a diameter of 150 mm. The polyurethane tread of the wheel guarantees low rolling resistance and quiet running! The load capacity is 500 kg.

TECHNICAL DATA

Castors diameter mm	150
Material	PU
Status	New
Outside dimension lenght	150
Outside dimension width	50
Outside dimension height	190
Carry weight	500
Product	new
Туре	Wheels

PRODUCT DESCRIPTION

A strong transport wheel with a load capacity of 500 kg. This makes it extremely suitable for both light and heavy transport, even on less slippery floors! The wheel tread is made of cast polyurethane (PU) with a cast iron core (painted black). The hardness of the tread is 90° - 98° Sh.A (HARD). As a result, the castor wheel guarantees low rolling resistance and low-noise running. In addition, this castor wheel is wear-resistant and streak-free. The wheel comes with mounting plate with the dimensions 135×110 mm. The axle hole diameter is 20 mm and the overall height of the castor wheel is 190 mm. This wheel has a tread width of 50 mm and the center distance of the mounting holes is $105 \times 80/75$ mm. The diameter of the mounting holes is $11 \times 105 \times$

























PRODUCT SPECIFICATION SHEET

The construction is equipped with a central kingpin, making it very suitable for regular peak loads! These castor wheels with polyurethane tread are suitable as an alternative to vulcanized natural rubber when certain chemicals, oils and greases play a role. In addition, this wheel can be mounted under every roll container and dolly in our range. Would you like to learn more about points to consider when buying wheels? Then read our blog with tips when purchasing!

Link to visit this page:

https://rotom.co.uk/swivel-castor-pu-o-150-mm-with-ball-bearing-500-kg-48413





















