

# PRODUCT SPECIFICATION SHEET



#### **APPLICABLE SERVICES**



#### **REPAIR AND MAINTENANCE**

This product can be repaired or maintained. Contact us for more details

## Fixed castor PA Ø 100 mm - with ball bearing, 500 kg

## SKU 48442

This fixed castor has a ball bearing with a diameter of 100 mm. The hard nylon tread of the fixed castor guarantees the very best rolling properties on slippery floors. Wear-resistant, shock-resistant and a high load capacity of 500 kg.

#### **TECHNICAL DATA**

Castors diameter mm	100
Material	PA
Status	New
Outside dimension lenght	100
Outside dimension width	38
Outside dimension height	130
Carry weight	500
Product	new
Туре	Wheels

## PRODUCT DESCRIPTION

A strong transport wheel that has a load capacity of 500 kg. The tread of the wheel is made of nylon and the hardness of this tread is  $70^{\circ} \pm 5^{\circ}$  Sh.D (EXTRA HARD). This makes it extremely suitable for heavy transport on smooth floors. The wheel is wear-resistant, shock-resistant and streak-free! The wheel comes with mounting plate with the dimensions  $105 \times 86$  mm. The bore diameter is 15 mm and the height of the fixed castor is 130 mm. This wheel has a tread width of 38 mm and the center distance of the mounting holes is  $82/77 \times 60$  mm. The material of the fork (type: MD50) consists of galvanized steel. The weight of this fixed castor is 1.38 kg. In addition, this wheel can be mounted under every roll container and dolly in our range. The material of the fixed castor consists of plastic polyamide and the temperature range of the wheel is  $-30^{\circ}$ C to  $+80^{\circ}$ C. When purchasing wheels, you can take into account various

























# **PRODUCT SPECIFICATION SHEET**

points, so that you purchase the right wheels with the properties you are looking for! Would you like to learn more about these points of interest? Then read our blog with tips when purchasing!

## Link to visit this page:

https://rotom.co.uk/fixed-castor-pa-o-100-mm-with-ball-bearing-500-kg-48442





















