



Transport wheel PA heavy Ø 125 mm - with ball bearing, 700 kg

SKU 48444

This loose wheel is equipped with a ball bearing with a diameter of 125 mm. The hard nylon tread of the wheel guarantees the very best rolling properties on slippery floors. Wear-resistant, shock-resistant and a high load capacity of 700 kg.

TECHNICAL DATA

Castors diameter mm	125
Material	PA
Status	New
Outside dimension length	125
Outside dimension width	45
Outside dimension height	125
Carry weight	700
Product	new
Type	Wheels

APPLICABLE SERVICES



REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

PRODUCT DESCRIPTION

A strong transport wheel that has a load capacity of 700 kg. The tread of the wheel is made of nylon, the hardness of the tread is 70° ±5° Sh.D (EXTRA HARD). This makes it extremely suitable for heavy transport on smooth floors. The axle hole diameter of the transport wheel is 15 mm, the tread width is 45 mm. The diameter of the ball bearing fitting is 35mm and the depth is 12mm. The installation length of the wheel is 48 mm. The hub diameter of the transport wheel is 58 mm and the hub length is 50 mm. The wheel is wear-resistant and shock-resistant. The material of the transport wheel consists of plastic polyamide and the temperature range is -30° C to +80° C. Its own weight is only 0.53 kg. In addition, this wheel can be mounted under every roll container and dolly in our range. A combination of the above properties makes the wheel



very suitable for use in the food industry, for example at fish or meat processing companies. Would you like to learn more about the different types of wheels from LogistiekOnline? Then read our blog about buying tips !

Link to visit this page:

<https://rotom.co.uk/transport-wheel-pa-heavy-o-125-mm-with-ball-bearing-700-kg-48444>

