



**Swivel castor PA Ø 125 mm - with ball bearing, 500 kg**

**SKU 48445**

This swivel castor has a ball bearing with a diameter of 125 mm. The hard nylon tread of the wheel guarantees the very best rolling properties on slippery floors. Wear-resistant, shock-resistant and a high load capacity of 500 kg.

**TECHNICAL DATA**

<b>Castors diameter mm</b>	125
<b>Material</b>	PA
<b>Status</b>	New
<b>Outside dimension length</b>	125
<b>Outside dimension width</b>	45
<b>Outside dimension height</b>	156
<b>Carry weight</b>	500
<b>Product</b>	new
<b>Type</b>	Wheels

**APPLICABLE SERVICES**



**REPAIR AND MAINTENANCE**

This product can be repaired or maintained. Contact us for more details

**PRODUCT DESCRIPTION**

A strong transport wheel with plate attachment that has a load capacity of 500 kg. The tread of the castor wheel is made of nylon, the hardness of this tread is 70° ±5° Sh.D (EXTRA HARD). This makes it extremely suitable for heavy transport on smooth floors without barriers and dirt! The wheel comes with mounting plate with the dimensions 105 x 86 mm. The axle hole diameter is 15 mm and the overall height of the castor wheel is 156 mm. This wheel has a tread width of 45 mm and the center distance of the mounting holes is 82/77 x 60 mm. The diameter of the mounting holes is 9 mm and the dimension of the inner fork width is 50 mm. The construction of the castor wheel has a central kingpin, making it very suitable for regular peak loads! The weight of the castor wheel is 1.42 kg. In addition, this wheel can be mounted under every roll container and dolly in our range. The material of the fork (type: MD50)



consists of galvanized steel. The material of the castor is made of plastic polyamide and the temperature range is  $-30^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$ . Would you like to learn more about the different types of wheels from LogistiekOnline? Then read our blog about buying tips !

Link to visit this page:

<https://rotom.co.uk/swivel-castor-pa-o-125-mm-with-ball-bearing-500-kg-48445>

