



## Fixed castor PA Ø 125 mm - with ball bearing, 500 kg

SKU 48446

This fixed castor has a ball bearing with a diameter of 125 mm. The hard nylon tread of the fixed castor guarantees the very best rolling properties on slippery floors. Wear-resistant, shock-resistant and a high load capacity of 500 kg.

### TECHNICAL DATA

<b>Castors diameter mm</b>	125
<b>Material</b>	PA
<b>Status</b>	New
<b>Outside dimension length</b>	125
<b>Outside dimension width</b>	45
<b>Outside dimension height</b>	156
<b>Carry weight</b>	500
<b>Product</b>	new
<b>Type</b>	Wheels

### APPLICABLE SERVICES



#### REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

### PRODUCT DESCRIPTION

A strong transport wheel that has a load capacity of 500 kg. The tread of the wheel is made of nylon, the hardness of the tread is 70° ±5° Sh.D (EXTRA HARD). This makes it extremely suitable for heavy transport on smooth floors. The wheel is wear-resistant, shock-resistant and streak-free! The wheel comes with mounting plate with the dimensions 105 x 86 mm. The bore diameter is 15 mm and the height of the fixed castor is 156 mm. This wheel has a tread width of 45 mm and the center distance of the mounting holes is 82/77 x 60 mm. The own weight of this fixed castor is 1.05 kg. In addition, this wheel can be mounted under every roll container and dolly in our range. The material of the fork (type: MD50) consists of galvanized steel. The material of the fixed castor consists of plastic polyamide and the temperature range of the wheel is -30°C to +80°C. Would you like to learn more about the different types of wheels



from LogistiekOnline? Then read our blog about buying tips !

Link to visit this page:

<https://rotom.co.uk/fixed-castor-pa-o-125-mm-with-ball-bearing-500-kg-48446>

