



Swivel castor PA Ø 125 mm - with ball bearing and brake, 500 kg

SKU 48447

This swivel castor with brake is equipped with a ball bearing with a diameter of 125 mm. The hard nylon tread of the wheel guarantees the very best rolling properties on slippery floors. Wear-resistant, shock-resistant and a high load capacity of 500 kg

TECHNICAL DATA

Castors diameter mm	125
Material	PA
Status	New
Outside dimension length	125
Outside dimension width	45
Outside dimension height	156
Carry weight	500
Product	new
Type	Wheels

APPLICABLE SERVICES



REPAIR AND MAINTENANCE
This product can be repaired or maintained. Contact us for more details

PRODUCT DESCRIPTION

A strong transport wheel with plate attachment that has a load capacity of 500 kg. The caster wheel tread is made of nylon, the tread hardness is 70° ±5° Sh.D (EXTRA HARD). This makes it extremely suitable for heavy transport on smooth floors without barriers and dirt! The wheel is wear-resistant, shock-resistant and also equipped with a foot brake at the rear! The wheel comes with mounting plate with the dimensions 105 x 86 mm. The axle hole diameter is 15 mm and the overall height of the castor wheel is 156 mm. The tread width is 45 mm and the center distance of the mounting holes is 82/77 x 60 mm. The diameter of the mounting holes is 9 mm and the dimension of the inner fork width is 50 mm. The construction of the castor wheel has a central kingpin, making it very suitable for regular peak loads! The weight of this swivel castor



with brake is 1.63 kg. In addition, this wheel can be mounted under every roll container and dolly in our range. The material of the fork (type: MD50) consists of galvanized steel. The material of the castor is made of plastic polyamide and the temperature range is -30°C to $+80^{\circ}\text{C}$. Would you like to learn more about the different types of wheels from LogistiekOnline? Then read our blog about buying tips !

Link to visit this page:

<https://rotom.co.uk/swivel-castor-pa-o-125-mm-with-ball-bearing-and-brake-500-kg-48447>

