



Swivel castor PA Ø 150 mm - with ball bearing, 700 kg

SKU 48449

This swivel castor is equipped with a ball bearing with a diameter of 150 mm. The hard nylon tread of the wheel guarantees the very best rolling properties on slippery floors. Wear-resistant, shock-resistant and a high load capacity of 700 kg.

TECHNICAL DATA

Castors diameter mm	150
Material	PA
Status	New
Outside dimension length	150
Outside dimension width	50
Outside dimension height	190
Carry weight	700
Product	new
Type	Wheels

APPLICABLE SERVICES



REPAIR AND MAINTENANCE
This product can be repaired or maintained. Contact us for more details

PRODUCT DESCRIPTION

A strong transport wheel with plate attachment that has a load capacity of 700 kg. The caster wheel tread is made of nylon, the tread hardness is 70° ±5° Sh.D (EXTRA HARD). This makes it extremely suitable for heavy transport on smooth floors without barriers and dirt! The wheel comes with mounting plate with the dimensions 135 x 110 mm. The axle hole diameter is 20 mm and the overall height of the castor wheel is 190 mm. This wheel has a tread width of 50 mm and the center distance of the mounting holes is 105 x 80/75 mm. The diameter of the mounting holes is 11 mm and the dimension of the inner fork width is 63.5 mm. The construction of the castor wheel has a central kingpin, making it very suitable for regular peak loads! The weight of the castor wheel is 2.67 kg. In addition, this wheel can be mounted under every roll container and dolly in our range. The material of the fork (type: MD70) consists of



galvanized steel. The material of the castor is made of plastic polyamide and the temperature range is -30°C to +80°C. LogistiekOnline has a wide range of roll container wheels. The suitable wheel can contribute to a smooth and easy logistics process, view our blog about buying tips here !

[Link to visit this page:](#)

<https://rotom.co.uk/swivel-castor-pa-o-150-mm-with-ball-bearing-700-kg-48449>

