



**Fixed castor PA Ø 100 mm - with ball bearing, 800 kg**

**SKU 48463**

This fixed castor has a ball bearing with a diameter of 100 mm. The hard nylon tread of the fixed castor guarantees the very best rolling properties on slippery floors. Wear-resistant, shock-resistant and a high load capacity of 800 kg.

**TECHNICAL DATA**

<b>Castors diameter mm</b>	100
<b>Material</b>	PA
<b>Status</b>	New
<b>Outside dimension length</b>	100
<b>Outside dimension width</b>	45
<b>Outside dimension height</b>	140
<b>Carry weight</b>	800
<b>Product</b>	new
<b>Type</b>	Wheels

**APPLICABLE SERVICES**



**REPAIR AND MAINTENANCE**

This product can be repaired or maintained. Contact us for more details

**PRODUCT DESCRIPTION**

A strong transport wheel that has a load capacity of 800 kg. The tread of the wheel is made of nylon, the hardness of the tread is 70° ±5° Sh.D (EXTRA HARD). This makes it extremely suitable for heavy transport on smooth floors. The wheel is wear-resistant, shock-resistant and streak-free! The wheel comes with mounting plate with the dimensions 105 x 86 mm. The bore diameter is 20 mm and the construction height of the fixed castor is 140 mm. This wheel has a tread width of 45 mm and the center distance of the mounting holes is 80/77 x 60 mm. The own weight of this fixed castor is 1.37 kg. In addition, this wheel can be mounted under every roll container and dolly in our range. The material of the fork (type: HD80) consists of galvanized steel. The material of the fixed castor consists of high-quality polyamide and the temperature range of the wheel is -30°C to +80°C. When purchasing wheels, you can



take into account various points that can greatly increase the ease of use and applications of a roll container. Would you like to learn more about these points of interest? Then read our blog with tips when purchasing !

[Link to visit this page:](#)

<https://rotom.co.uk/fixed-castor-pa-o-100-mm-with-ball-bearing-800-kg-48463>

