



Fixed castor PA Ø 125 mm - with ball bearing, 800 kg

SKU 48468

This fixed castor has a ball bearing with a diameter of 125 mm. The hard nylon tread of the fixed castor guarantees the very best rolling properties on slippery floors. Wear-resistant, shock-resistant and a high load capacity of 800 kg.

TECHNICAL DATA

Castors diameter mm	125
Material	PA
Status	New
Outside dimension length	125
Outside dimension width	50
Outside dimension height	165
Carry weight	800
Product	new
Type	Wheels

APPLICABLE SERVICES



REPAIR AND MAINTENANCE

This product can be repaired or maintained. Contact us for more details

PRODUCT DESCRIPTION

A strong transport wheel that has a load capacity of 800 kg. The tread of the wheel is made of nylon, the hardness of the tread is 70° ±5° Sh.D (EXTRA HARD). This makes it extremely suitable for heavy transport on smooth floors. The wheel is wear-resistant, shock-resistant and streak-free! The wheel comes with mounting plate with the dimensions 105 x 86 mm. The bore diameter is 20 mm and the construction height of the fixed castor is 165 mm. This wheel has a tread width of 50 mm and the center distance of the mounting holes is 80/77 x 60 mm. The own weight of this fixed castor is 1.67 kg. In addition, this wheel can be mounted under every roll container and dolly in our range. The material of the fork (type: HD80) consists of galvanized steel. The material of the fixed castor consists of plastic polyamide and the temperature range of the wheel is -30°C to +80°C. When purchasing wheels, you can take



into account various points that can greatly increase the ease of use and applications of a roll container. Would you like to learn more about these points of interest? Then read our blog with tips when purchasing !

Link to visit this page:

<https://rotom.co.uk/fixed-castor-pa-o-125-mm-with-ball-bearing-800-kg-48468>

