



**Fixed castor elastic rubber Ø 200 mm - with ball bearing, 400 kg**

**SKU 48483**

This fixed castor has a ball bearing with a diameter of 200 mm. The tread consists of unvulcanized black elastic natural rubber and partly due to the low-noise running, this wheel meets the highest ergonomic standards!

**TECHNICAL DATA**

<b>Castors diameter mm</b>	200
<b>Material</b>	Rubber
<b>Status</b>	New
<b>Outside dimension length</b>	200
<b>Outside dimension width</b>	50
<b>Outside dimension height</b>	238
<b>Carry weight</b>	400
<b>Product</b>	new
<b>Type</b>	Wheels

**APPLICABLE SERVICES**



**REPAIR AND MAINTENANCE**

This product can be repaired or maintained. Contact us for more details

**PRODUCT DESCRIPTION**

A strong transport wheel that has a load capacity of 400 kg. The wheel tread is made of vulcanised black elastic natural rubber and the tread hardness is 65° - 75° Sh.A (COMFORT). The tread is very wear resistant and the adhesion to the core is perfect. Because the tread is very elastic, the rolling properties are excellent even under maximum load. In addition, this wheel is streak-free! The wheel comes with mounting plate with the dimensions 135 x 110 mm. The axle hole diameter is 20 mm and the overall height of the castor wheel is 238 mm. This wheel has a tread width of 50 mm and the center distance of the mounting holes is 105 x 80/75 mm. The diameter of the mounting holes is 11 mm and the dimension of the inner fork width is 63.5 mm. The construction of the fixed castor is very suitable for regular peak loads! The own weight of the



fixed castor is 2.60 kg. In addition, this wheel can be mounted under every roll container and dolly in our range. The material of the fork (type: MD50) consists of galvanized steel and the temperature range is  $-20^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$ . This wheel is very suitable for use on moderate to poor surfaces. Application takes place under roll containers, industrial waste containers and other means of transport that are frequently and long-term loaded. The wheel is also specially designed and suitable for mounting ball bearings with an extra splash-proof seal in order to additionally guarantee lifespan, hygiene and maintenance-free use. Wheels are available in various shapes and sizes for different applications, so read more about tips here when purchasing!

[Link to visit this page:](#)

<https://rotom.co.uk/fixed-castor-elastic-rubber-o-200-mm-with-ball-bearing-400-kg-48483>

